



METERING VALVE DAV 400

The metering valve **DAV 400** is designed to dispense with the highest accuracy and repeatability greases and lubricants to NLGI 3 (1,000,000 mPa s). The chamber has a volumetric capacity adjustable from 1,0 to 6,0 cm³ and with a special sensor is possible to check the emptying of the dosing chamber, for the highest control of the assembly process.



DAV TECH SRL

Via Ravizza, 30
36075 Montecchio Maggiore (VI) - ITALY
Tel. 0039 0444 574510
Fax 0039 0444 574324

davtech@davtech.it
www.davtech.it

FIELDS OF APPLICATION:

- > Grease metering
- > Lubricants metering

FEATURES:

- > Volumetric dosing, reliable and constant
- > Dosing independent of viscosity, pressure and temperature of the lubricant
- > Pressure control system not necessary
- > Dosing objectivable with a sensor
- > Quantity dispensed easily adjustable and that can't be changed accidentally using the block screw
- > Pressure control system not needed

Technical Data

Model	DAV 400
Operation mode	Double Acting
Weight	710 g
Fluid pressure inlet	20 bar Min - Max 200 bar (low pressure version available)
Quantity dispensable	1,0 cm ³ - 6,0 cm ³
Actuating air pressure	5 - 7 bar
Inlet air	M3 fittings for ø 4mm hose
Inlet fluid thread	1/4 gas
Outlet fluid	1/8 female
Speed	Up to 60 cycles / min
Adjusting the amount dosed	Micrometric with block screw
Used materials	Stainless steel, anodized aluminum
Fluids to be dispensed	Greases and lubricants up to NLGI 3-1.000.000 mPa s

FEEDING PUMPS FOR GREASE

DAV Tech pumps are ideal to feed grease and lubricants, contained in cans or drums, to the valve DAV 400. Pumps are available for cans from 0.5 up to 5 kg and for 5 to 200 kg drums.

NOZZLES FOR VALVE DAV 400

The valve DAV 400 is equipped with threaded outlet 1/8 BSP female, where is possible to fit any kind of nozzle. We can also design and build special nozzles (multi-point, radial, etc.) to meet the customer needs.

DRIVE THE VALVE DAV 400

The DAV 400 valve have to be controlled by 5/2 solenoid valve. It is not necessary that the timing is accurate, but it is important that the time set in the two phases of operation allows the valve to recharge and to dispense the lubricant.

SENSOR FOR VALVE DAV 400

Through a simple reed switch (optional), you can verify a successful emptying of the volumetric chamber, to have the highest control of the assembly process.



Connection diagram

