

## METERING VALVE DAV 300

The metering valve **DAV 300** is designed to dispense with the highest accuracy and repeatability greases and lubricants to NLGI 3 (1,000,000 mPa s). The chamber has a volumetric capacity adjustable from 0,1 to 2,0 cm<sup>3</sup> and with a special sensor is possible to check the emptying of the dosing chamber, for the highest control of the assembly process.



### DAV TECH SRL

Via Ravizza, 30  
36075 Montecchio Maggiore (VI) - ITALY  
Tel. 0039 0444 574510  
Fax 0039 0444 574324

[davtech@davtech.it](mailto:davtech@davtech.it)  
[www.davtech.it](http://www.davtech.it)

### FIELDS OF APPLICATION:

- > Grease metering
- > Lubricants metering

### FEATURES:

- > Volumetric dosing, reliable and constant
- > Dosing independent of viscosity, pressure and temperature of the lubricant
- > Pressure control system not necessary
- > Dosing objectivable with a sensor
- > Quantity dispensed easily adjustable and that can't be changed accidentally using the block screw
- > Pressure control system not needed.

### Technical Data

<b>Model</b>	DAV 300
<b>Operation mode</b>	Double Acting
<b>Weight</b>	730 g
<b>Fluid pressure inlet</b>	20 bar Min - Max 200 bar (low pressure version available)
<b>Quantity dispensable</b>	0,1 cm <sup>3</sup> - 2,0 cm <sup>3</sup>
<b>Actuating air pressure</b>	5 - 7 bar
<b>Inlet air</b>	M3 fittings for ø 4mm hose
<b>Inlet fluid thread</b>	1/4 BSP
<b>Outlet fluid</b>	1/4 BSP
<b>Speed</b>	Up to 60 cycles/min
<b>Adjusting the amount dosed</b>	Micrometric with block screw
<b>Used materials</b>	Stainless steel, anodized aluminum
<b>Fluids to be dispensed</b>	Greases and lubricants up to NLGI 3-1.000.000 mPa s

## FEEDING PUMPS FOR GREASE

DAV Tech pumps are ideal to feed grease and lubricants, contained in cans or drums, to the valve DAV 300. Pumps are available for cans from 0.5 up to 5 kg and for 5 to 200 kg drums.

## NOZZLES FOR VALVE DAV 300


The valve DAV 300 is equipped with threaded outlet 1/8 BSP female, where is possible to fit any kind of nozzle. We can also design and build special nozzles (multi-point, radial, etc.) to meet the customer needs.

## DRIVE THE VALVE DAV 300

The DAV 300 valve have to be controlled by 5/2 solenoid valve. It is not necessary that the timing is accurate, but it is important that the time set in the two phases of operation allows the valve to recharge and to dispense the lubricant.

## SENSOR FOR VALVE DAV 300

Through a simple reed switch (optional), you can verify a successful emptying of the volumetric chamber, to have the highest control of the assembly process.



### Connection diagram

